

AXIS Camera Station S1148 Recorder

Out-of-the box ready server for UHD surveillance

AXIS Camera Station S1148 Recorder is an out-of-the-box ready rack server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1148 is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 48 channels plus all necessary software. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide portfolio of video surveillance devices. With redundant enterprise-grade hard disks and power supplies, operating system stored on solid-state drive (SSD), and expandable storage, AXIS S1148 provides high-performance and reliability for your system.

- > Ease of installation
- > AXIS Camera Station licenses included
- > Full compatibility with Axis products
- > Available with 24TB/ 64TB/ 144TB storage
- > 5-year warranty



WWW.CXIS.COM T10131091/EN/M11.2/2201

	AXIS Camera Stat	ion \$1148	Recorder
Models	S1148 24 TB S1148 64 TB S1148 140 TB	Connectors	2 x 750 W hot-plug redundant power supplies (included) (100-240 V AC, 10 - 5 A, 50/60 Hz)
Licenses	48 AXIS Camera Station core licenses included and tied to the hardware. Can be upgraded with additional licenses (sold separately).	Connectors	Tront side: 1x USB 3.1 Type-C 2x USB 2.0 1x VGA Rear side: 2x USB 3.1 2x Ethernet (RJ45) 1 GbE 1x VGA 1x Serial port
System scalability	Qualified for up to 64 video channels and 128 doors		
Hardware			
Processor	Intel® Xeon® Silver		
Memory	S1148 24 TB 8 GB	Video	
	S1148 64 TB 16 GB S1148 140 TB 32 GB	Video streaming	Not intended for local viewing of video. Recommended to use AXIS desktop terminals.
Storage	S1148 24 TB Hot swappable Enterprise Class HDD Total HDD slot: 8 Free HDD slot: 2 Out-of-the-box storage: 20 TB after RAID 5 Out-of-the-box capacity without RAID: 24 TB (6x4 TB) S1148 64 TB Hot swappable Enterprise Class HDD Total HDD slot: 12 Free HDD slot: 4 Out-of-the-box storage: 56 TB after RAID 5 Out-of-the-box capacity without RAID: 64 TB (8x8 TB) S1148 140 TB Hot swappable Enterprise Class HDD Total HDD slot: 12 Free HDD slot: 15 Free HDD slot: 15 Free HDD slot: 16 Out-of-the-box capacity without RAID: 144 TB (12x12 TB) a S1148 24 TB Factory RAID level: 5 RAID levels: 0, 1, 5, 6, 10 S1148 64 TB Factory RAID level: 5 RAID levels: 0, 1, 5, 6, 10 S1148 140 TB Factory RAID level: 6 DAN Levels: 0, 1, 5, 6, 10 S1148 Indianal State Class HDD Factory RAID level: 6 DAN Levels: 0, 1, 5, 6, 10 S1148 Indianal State Class HDD Factory RAID level: 6 DAN Levels: 0, 1, 5, 6, 10 S1148 Indianal State Class HDD Factory RAID level: 6 DAN Levels: 0, 1, 5, 6, 10 S1148 Indianal State Class HDD Factory RAID level: 6 DAN Levels: 0, 1, 5, 6, 10 S1148 Indianal State Class HDD Factory RAID level: 6 DAN Levels: 0, 1, 5, 6, 10	Recording	Qualified for recording up to 64 video channels with a total recording rate up to 512 Mbit per second.
		General	
		Operating system	Microsoft® Windows® 10 IoT Enterprise SAC Built-in operating system recovery: yes Operating system drive: 240 GB SSD
		Operating conditions	10 °C to 35 °C (50 °F to 95 °F) Humidity 20–80% RH (non-condensing)
		Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
		Approvals	EMC EN 55032 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), RCM AS/NZS CISPR 32 Class A, VCCI Class A, KC KN 32 Class A KC KN 35 Safety IEC/EN/UL 60950-1, EN 62368-1, NOM, BSMI, EAC
		Dimensions	681 x 482 x 87 mm (26.82 x 19 x 3.43 in), 2U chassis
		Weight	S1148 24 TB 20.3 kg (45 lb) S1148 64 TB 22.3 kg (49 lb) S1148 140 TB 26.5 kg (58 lb)
		Included accessories	Rack rails, 2x C13 to C14 power cords for rack PDU (Wall plug power cords are not included)
Power	RAID levels: 0, 1, 5, 6, 10 S1148 24 TB 2 x 495 W hot-plug redundant power supplies (included) (100-240 V AC, 6.5 - 3 A, 50/60 Hz) S1148 64 TB	Optional accessories	Axis desktop terminals For more accessories, see axis.com
		Warranty a. Prior to Q2 2020:	5-year warranty, see axis.com/warranty
	2 x 750 W hot-plug redundant power supplies (included) (100-240 V AC, 10 - 5 A, 50/60 Hz) S1148 140 TB	a. F1101 to Q2 2020:	ום טוגדון טו טדו (פו טוגדון טו טדו

AXIS Camera Station

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on axis.com

Environmental responsibility: axis.com/environmental-responsibility

