

Part No **41068**

DISPLAYPORT 1.2 TO HDMI 18G ACTIVE CONVERTER

CONVERT A DISPLAYPORT 1.2 SIGNAL TO HDMI 2.0 18G



DESCRIPTION RELATED PRODUCTS

N/A

- Connect a DisplayPort computer to an HDMI 4k display
- Supports resolutions up to 3840x2160@60Hz
- Audio pass-through if supported by the video source
- Active chipset for enhanced compatibilty with various graphic cards
- 2 year warranty

The Lindy DisplayPort to HDMI Converter is a high performance solution that allows a DisplayPort source device to be connected to a HDMI display or projector. It supports full 4K Ultra HD resolutions up to 3840x2160@60Hz 4:4:4 8bit and HDMI 2.0 with up to 18Gbps bandwidth, making it the ideal tool for high-resolution tasks like editing 4K videos.

HDCP 2.2 ensures issue-free playback of a variety of 4K Ultra HD movies, TV shows and other 4K content as well as existing Full HD signals

Active conversion guarantees compatibility with various graphics cards including AMD Eyefinity, NVIDIA surround and Intel Collage, great for an immersive gaming setup or a productive multi-screen working experience.



DISPLAYPORT 1.2 TO HDMI 18G ACTIVE CONVERTER

SPECIFICATIONS

AV Interface DisplayPort to HDMI

DisplayPort 1.2 / HDMI 2.0a Interface Standard

18Gbps **Supported Bandwidth**

Maximum Input Resolution 3840x2160@60Hz 4:4:4 8bit

3840x2160@60Hz 4:4:4 8bit **Maximum Output Resolution**

Chipset PS176

HDCP Support HDCP 2.2 Supported Audio Pass-through

Separate Audio Ports Special Features

CONNECTORS

Input DisplayPort Male

Output **HDMI Type A Female**

MISCELLANEOUS

Packaging Type Polybag

Packaging Dimension 160x160x20mm (6.3x6.3x0.79in)

Gross Weight 0.045kg (0.1lb)

Warranty (Years)

Certificated CE, FCC, RoHS &REACH

PHYSICAL PROPERTIES

Cable Length

45x45x15mm Dimensions (approx.) WxDxH

> (1.77x1.77x0.59in) 31.5x20x9mm

(1.24x0.79x0.35in) / DP

150mm (5.91in)

TPE **Housing Material**

PVC **Jacket Material Jacket Diameter**

5mm (0.2in) **Minimum Bend Radius** 55mm (2.17in) 0.020kg (0.04lb) **Net Weight**

0°C - 70°C (32°F - 158°F) **Operating Temperature** -20°C - 70°C (-4°F - 158°F) Storage Temperature 10 - 90% RH (non-condensing) **Humidity**

Black Colour

PURCHASING INFORMATION

41068 No.

4002888410687 EAN

PACKAGING CONTENTS

DisplayPort 1.2 to HDMI 2.0 18G Active

Converter