

PIN Assignment


P1	P2
8	1
3	2
2	3
20	4
7	5
6	6
4	7
5	8
22	9
SHIELD	SHIELD

ELECTRICAL TESTING:

- 1) 100% open short & miss wire test.
- 2) Insulation Resistance: ≥5MΩ.
- 3) Contact Resistance: 5Ω.
- 4) Connector: Insertion/extraction durability: 5000 cycles minimum

⑥	SR- SIDE	45P PVC,Beige Jacket	g	
⑤	SCREW	4-40UNC	PCS	4
④	SR-OUT SIDE	45P PVC,Beige	g	
③	SR-INNER SIDE	TRANSPARENT PE	g	
②	CONNECTOR	DB 9P MALE,PLATED WITH NICKEL	PCS	1
①	CONNECTOR	DB 25P FEMALE,PLATED WITH NICKEL	PCS	1
ITEM	P/N	DESCRIPTION	UNIT	QTY

THIRD ANGLE PROJECTION



GENERAL NOTES

DIMENSIONS ARE IN MM - DO NOT SCALE
 THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION THAT IS PROPERTY OF STARTECH.COM

StarTech.com

PRODUCT ID	AT925MF		
DESCRIPTION	DB9 to DB25 Serial Adapter - M/F		
REV: A	DO NOT SCALE	SHEET : 1 OF: 1	DATE: 06/18/2020