



### Overview

Model Name	APC Back-UPS 500VA,AVR, IEC outlets
Includes	User Manual
Standard Lead Time	Usually in Stock
Product Distribution	Albania , Algeria , Andorra , Angola , Armenia , Austria , Azerbaijan , Bahrain , Belarus , Belgium , Benin , Bosnia And Herzegovina , Botswana , Bulgaria , Burkina Faso , Burundi , Cameroon , Central African Republic , Chad , Congo , CONGO, THE DEMOCRATIC REPUBLIC OF THE , <![CDATA[Cote D'Ivoire]]> , Croatia , Cyprus , Czech Republic , Denmark , Djibouti , Egypt , Equatorial Guinea , Eritrea , Estonia , Ethiopia , France , Gabon , Gambia , Georgia , Germany , Ghana , Gibraltar , Greece , Guadeloupe , Guinea , French Guiana , Hungary , Iceland , Iran (Islamic Republic Of) , Iraq , Ireland , Israel , Italy , Jordan , Kazakhstan , Kenya , Kuwait , Latvia , Lebanon , Lesotho , Liberia , Liechtenstein , Lithuania , Luxembourg , Macedonia , Madagascar , Malawi , Mali , Malta , Martinique , Mauritania , Mauritius , Mayotte , Moldova, Republic Of , Mongolia , Morocco , Mozambique , Namibia , Netherlands , Niger , Nigeria , Oman , Pakistan , Poland , Portugal , Qatar , Reunion , Romania , Russian Federation , Rwanda , Saudi Arabia , Senegal , Sierra Leone , Slovakia (Slovak Republic) , Slovenia , Somalia , South Africa , Spain , Sudan , Suriname , Tajikistan , TANZANIA, UNITED REPUBLIC OF , Togo , Turkey , Turkmenistan , Turks And Caicos Islands , Uganda , Ukraine , United Arab Emirates , Uzbekistan , Western Sahara , Yemen , Zambia , Zimbabwe

### Output

Output Power Capacity	300 Watts / 500 VA
Max Configurable Power (Watts)	300 Watts / 500 VA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	50 Hz
Output Frequency (sync to mains)	Line Interactive
Waveform Type	Stepped approximation to a sinewave
Output Connections	(1) IEC Jumpers (Battery Backup) , (3) IEC 320 C13 (Battery Backup)

### Input

Nominal Input Voltage	230V
Input Frequency	45 - 65 Hz
Input Connections	IEC-320 C14
Cord Length	1.83 meters
Input voltage range for main operations	160 - 280 V

Maximum Input Current	2 A
Input Breaker Capacity	7 A

### Batteries & Runtime

Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	0 hour(s)
Replacement Battery	APCRBC114
RBC Quantity	0

### Communications & Management

Available SmartSlot™ Interface Quantity	0
Control panel	LED status display with On Line : On Battery : Replace Battery and Overload indicators
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

### Surge Protection and Filtering

Surge energy rating	273 joules
---------------------	------------

### Physical

Maximum Height	185.0 mm
Maximum Width	115.0 mm
Maximum Depth	213.0 mm
Rack Height	0 U
Net Weight	5.2 kg
Shipping Weight	5.68 kg
Shipping Height	257.0 mm
Shipping Width	190.0 mm
Shipping Depth	291.0 mm
Master Carton Units	2.0
Master Carton Weight	0.0 lbs
Color	Black
SCC Codes	6073130430736 7
Units per Pallet	60.0

### Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	45.000 dB

### Conformance

Approvals	CE , ENERGY STAR V1.0 (EU)
Standard warranty	2 years repair or replace

### Sustainable Offer Status

RoHS	Compliant
------	-----------

