

USB-C to HDMI Adapter - 4K 60Hz

Product ID: CDP2HD4K60SA



This is no ordinary video adapter. Yes, it enables you to connect the USB-C port on your computer to an HDMI display or projector, but it also features a unique Presentation Mode switch. When you turn on this switch, the adapter prevents your computer from launching its screen saver, going to sleep or entering power save mode. The adapter ensures that your screen will always stay on, making it the perfect USB-C video adapter for any presentation or meeting.

When you deliver a presentation, your goal is to engage with your audience, not your computer. But, if you don't move your mouse soon enough, or change your power settings, your screen goes black due to inactivity while you're addressing the audience. This can be a major distraction when you're trying to focus on the message you're communicating.

This adapter prevents screen disruptions with Presentation Mode, a unique feature that automatically initiates occasional cursor movement to prevent your computer's power settings from interrupting your presentation. It's perfect for sharing websites, drawings, spreadsheets, PDFs or slide shows during your meeting.

You can turn Presentation Mode on or off depending on your application. Turn it on when you're in the boardroom and want your screen to stay on, and turn it off when you're using the adapter at your workspace or office hot desk, to enable your computer's original power settings to take effect. Using the toggle switch is easy, and saves you the hassle of constantly making adjustments in your operating system settings.

To ensure easy operation and installation, this unique adapter is natively supported on Windows and Mac computers. It's easy to connect the adapter using the versatile USB Type-C port on your computer. The reversible USB-C connector means you will always plug it in correctly on your first try, which saves you the hassle and distraction of repeatedly attempting to connect your laptop to a display or projector.

This adapter lets you harness the video capabilities that are built into your computer's USB Type-C connection, to deliver astonishing UHD 4K 60Hz resolution to your HDMI 2.0 display. This makes it easier for you to multitask while you work on the most resource-demanding applications imaginable.

With this adapter, you can achieve an output resolution of up to 3840 x 2160p at 60Hz, which is perfect for performing high-resolution tasks such as viewing 4K video. Plus, the adapter is backward compatible with 1080p displays, which makes it a great travel accessory ensuring you can connect to any boardroom display or projector.



The CDP2HD4K60SA is backed by a 3-year StarTech.com warranty and free lifetime technical support.

Note: Your USB-C equipped device must support video to work with this adapter.

Certifications, Reports and Compatibility

Applications

• Be ready to present from your laptop, with the peace of mind in knowing your laptop will not enter power save mode when you don't want it to

- Keep this adapter with you while you travel to ensure you can connect to any HDMI display you come across
- Connect an HDMI display to your USB-C laptop to use as a secondary monitor

Features

• Equipped with a Presentation Mode feature to ensure your video output is not interrupted by your computer's power saving modes

• Avoid the hassle of adjusting power settings, with an easy-to-use toggle switch that lets you turn Presentation Mode on or off

- Works on Mac and Windows computers
- Support for Ultra HD video resolutions up to 4K at 60Hz
- Hassle-free connection with the reversible USB-C connector
- Maximum portability with a small footprint and lightweight design
- Thunderbolt 3 port compatible
- 7.1 audio support

Hardware			
	Warranty	3 Years	
	Ports	1	
	AV Input	USB-C	
	AV Output	HDMI - 2.0	

Performance



	Maximum Cable Distance To Display	23.0 ft [7 m]
	Maximum Digital Resolutions	3840 x 2160 (Ultra HD 4K) @ 60Hz
	Supported Resolutions	1024 x 768
		1280 x 720
		1920 x 1080
		1920 x 1200
		2560 x 1440
		2560 x 1600
		3840 x 2160
	Wide Screen Supported	Yes
	Audio Specifications	HDMI - 7.1 Channel Audio
Connector(s)		
	Connector A	USB-C (24 pin) DisplayPort Alt Mode
	Connector B	HDMI (19 pin)
Special Notes / Requirements	Connector B	HDMI (19 pin)
	Connector B System and Cable Requirements	HDMI (19 pin) Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter.
	System and Cable	Your USB-C port must support DisplayPort over USB-C (DP Alt
	System and Cable Requirements	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. This video adapter is not compatible with cables that use
Requirements	System and Cable Requirements	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. This video adapter is not compatible with cables that use
Requirements	System and Cable Requirements Note	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. This video adapter is not compatible with cables that use RedMere technology.
Requirements	System and Cable Requirements Note Operating Temperature	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. This video adapter is not compatible with cables that use RedMere technology. 5C to 35C (41F to 95F)
Requirements	System and Cable Requirements Note Operating Temperature Storage Temperature	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. This video adapter is not compatible with cables that use RedMere technology. 5C to 35C (41F to 95F) 5C to 35C (41F to 95F)
Requirements Environmental Physical	System and Cable Requirements Note Operating Temperature Storage Temperature	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. This video adapter is not compatible with cables that use RedMere technology. 5C to 35C (41F to 95F) 5C to 35C (41F to 95F)
Requirements Environmental Physical	System and Cable Requirements Note Operating Temperature Storage Temperature Humidity	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. This video adapter is not compatible with cables that use RedMere technology. 5C to 35C (41F to 95F) 5C to 35C (41F to 95F) 25% to 85% RH Non-Condensing



	Product Length	7.5 in [19.0 cm]
	Product Width	1.7 in [43.0 mm]
	Product Height	0.6 in [16.0 mm]
	Weight of Product	1.0 oz [28.0 g]
Packaging Information		
	Package Length	9.3 in [23.5 cm]
	Package Width	3.2 in [82.0 mm]
	Package Height	0.9 in [22.0 mm]
	Shipping (Package) Weight	2.4 oz [67.0 g]
What's in the Box		
	Included in Package	USB-C to HDMI video adapter
		quick-start guide

*Product appearance and specifications are subject to change without notice.

