

USB 2.0 DIGI-USB2

1-Port USB 2.0 100m (330 feet) Category 5e/6/6a/7 Extender Set with Flexible Power.

Quick Start Guide

Package Contents:

- (1) DIGI-USB2 Local Extender (LEX)
- (1) DIGI-USB2 Remote Extender (REX)
- (1) USB 2.0 Cable
- (1) AC Power Adapter
- (1) US, UK, AU and EU Power Cord
- (1) Quick Start Guide

For full User's Manual scan this QR Code:




Before you get started, ensure all drivers required for your remote USB device(s) are installed.

Step 1:

Place the units where desired and connect the solid core Category 5e/6/6a/7 extension link cabling into the Link ports (RJ45) of the Local and Remote extenders.


Step 2:

Connect the power adapter into the desired unit – LEX or REX. Only one side is powered, do not attempt to power both sides.



Step 3:

Connect the LEX into your computer using the included USB 2.0 A-B cable.



Step 4:

Attach your USB device to the REX.



Technical Specifications

I/O Connections	
USB	Type A and Type B
Twisted Pair	Shielded RJ45 Female
24V DC Power	5.5 mm Outside Diameter, 2.1 mm Inside Diameter Barrel
Maximum Distance	
CAT 5e/6/6a/7	100m (330')
Supported Signals	
USB 2.0	Up to 480 Mbps
USB 1.1	Up to 12 Mbps
Chassis and Environmental	
Enclosure	Black ABS with Rubberized coating
Dimensions	87.5mm x 65mm x 30mm (3.4 in. x 2.6 in. x 1.2 in.)
Shipping Weight	0.45kg (1 lbs.)
Operating Temperature	0° to +50° C (+32° to +122° F)
Operating Humidity	20% to 80%, Non-condensing
Storage Temperature	-20° to +70° C (-4° to +158° F)
Storage Humidity	10% to 90%, Non-condensing
Power, EMC, and Regulatory	
Power to USB Devices	1000mA
Maximum Power Consumption	5.0 watts
Power Supply	24VDC 1A
Regulatory	FCC (Class A), CE (Class A), RoHS2/3 (CE), Flammability V-0
Other	
Standard Warranty	5 Years
Included Accessories	USB cable, Power Supply, US, UK, AU and EU Power Cables, and Installation Guide
Mounting	Slots for cable ties

FCC Radio Frequency Interference Statement Warning

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received including interference that may cause undesired operation.

CE Statement

We, Liberty AV Solutions, declare under our sole responsibility that the DIGI-USB2, to which this declaration relates, is in conformity with European Standards EN 55024, EN 55032, EN 61000, and RoHS Directive 2011/65/EU + 2015/863/EU.

IC Statement

This Class A digital apparatus complies with Canadian ICES-003.

WEEE Statement

The European Union has established regulations for the collection and recycling of all waste electrical and electronic equipment (WEEE). Implementation of WEEE regulations may vary slightly by individual EU member states. Please check with your local and state government guidelines for safe disposal and recycling or contact your national WEEE recycling agency for more information.

Product Operation and Storage

Please read and follow all instructions provided with this product, and operate for intended use only. Do not attempt to open the product casing as this may cause damage and will void warranty. Use only the power supply provided with this product. When not in use, product should be stored in a dry location between -20°C and 70°C.

