

## USB-C to Parallel Printer Cable

**Product ID:** ICUSBCPLLD25



This USB-C to parallel printer cable allows you to connect your USB-C enabled laptop or desktop computer to a DB25 printer.

### Cost-saving solution

A cost-effective and reliable solution, the USB to DB25 adapter saves you the expense of replacing a parallel printer for the sake of USB compatibility. It turns an available USB-C port on your laptop or desktop computer into a DB25 female parallel port, allowing you to connect a DB25 printer to your computer as if the necessary parallel port was built-in.

### Easy installation and portability

The printer cable is supported by a broad range of operating systems, including Windows, Linux, and macOS, which makes it easy to integrate into mixed OS environments. It supports plug-and-play installation, saving you time and hassle.

The printer cable is USB powered, so there's no need for an external power adapter.

The ICUSBCPLLD25 is backed by a StarTech.com 2-year warranty and free lifetime technical support.

## Certifications, Reports and Compatibility

### Applications

- Enables you to quickly add a parallel port to your USB-C enabled laptop or computer, for use with printers with DB25 connectors
- Ideal solution for notebooks or desktop computers lacking a parallel port

## Features

- Connect your USB-C enabled laptop or desktop computer to a DB25 printer
- Compatible with Windows, Linux, and macOS
- Turns an available USB-C port on your laptop or desktop computer into a DB25 Female parallel port
- Easy plug-and-play installation

---

### Hardware

Warranty	2 Years
Ports	1
Interface	Parallel
Bus Type	USB-C
Chipset ID	Prolific - PL2305

---

### Performance

Maximum Data Transfer Rate	1.5Mbps
----------------------------	---------

---

### Connector(s)

Connector Type(s)	USB Type-C (24-pin) USB 2.0 (480Mbps) DB-25 (25 pin, D-Sub)
-------------------	--

---

### Software

OS Compatibility	Windows 7, 8.1, 10, 11 Windows Server 2008 R2, 2012 R2, 2016, 2019 macOS 10.11 and 10.15, 11.0, 12.0 Linux 2.6.x to 4.4x <i>LTS Versions only</i>
------------------	--

---


### Special Notes / Requirements

System and Cable Requirements	One available USB-C port
-------------------------------	--------------------------

---

### Power

Power Source	USB-Powered
--------------	-------------



---

**Environmental**

Operating Temperature	5C to 40C (41F to 140F)
Storage Temperature	-20C to 70C (-4F to 158F)
Humidity	0~80% RH non-condensing

---

**Physical Characteristics**

Color	Black
Product Length	6.1 ft [1.8 m]
Product Width	0.0 in [0.0 mm]
Product Height	0.0 in [0.0 mm]
Weight of Product	3.2 oz [92.0 g]

---

**Packaging Information**

Package Length	8.7 in [22.0 cm]
Package Width	7.9 in [20.0 cm]
Package Height	0.4 in [10.0 mm]
Shipping (Package) Weight	3.8 oz [108.0 g]

---

**What's in the Box**

Included in Package	parallel printer adapter cable
	quick-start guide

---

***\*Product appearance and specifications are subject to change without notice.***

