

Work Area

Category 5e – Loaded Faceplates

TrueNet® RJ-K LN Outlets

UK style faceplates featuring high-performance RJ-K LN unshielded modular jacks for LAN cabling systems satisfying Category 5e requirements.

Dimensions

Single: 85 high x 85 wide x 8mm deep
Single: 85 high x 145 wide x 8mm deep

Cable Parameters

Conductor diameter 0.4-0.65mm (AWG 22-26)
Cable diameter range with insulation 0.7-1.4mm

Test Specification

Exceeds specifications according to
ISO/IEC 11801:2002, EN 50173-1:2002
and TIA/EIA 568-B

Features

- Performance exceeding Category 5e specifications up to 100MHz
- Single, double and quad variants available
- Comes complete with jacks, faceplate and fixings in one box
- Swift terminations onto LSA-PLUS® IDC's
- Includes integrated dust protection in black or white

Ordering Information

| Description | Catalogue Number |
|--|------------------|
| Loaded Faceplate, Category 5e LN UTP, Single, White Shutter (Pack of 10) | 6538 1 111-13 |
| Loaded Faceplate, Category 5e LN UTP, Single, Black Shutter (Pack of 10) | 6538 1 112-13 |
| Loaded Faceplate, Category 5e LN UTP, Double, White Shutter (Pack of 10) | 6538 1 111-14 |
| Loaded Faceplate, Category 5e LN UTP, Double, Black Shutter (Pack of 10) | 6538 1 112-14 |
| Loaded Faceplate, Category 5e LN UTP, Quad, White Shutter (Pack of 10) | 6538 1 111-17 |
| Loaded Faceplate, Category 5e LN UTP, Quad, Black Shutter (Pack of 10) | 6538 1 112-17 |

