

10 ft Mini DisplayPort to VGA Adapter Converter Cable - mDP to VGA 1920x1200 - Black

Product ID: MDP2VGAMM10B



The MDP2VGAMM10B 10ft active Mini DisplayPort to VGA converter cable lets you connect your Mini DisplayPort-equipped device (Mac, Ultrabook or any mDP enabled Microsoft Surface Pro) directly to a VGA monitor or projector with no additional adapters or cables required -- a cost-effective solution for enabling your Mini DisplayPort computer to work with a VGA monitor or projector.

The adapter cable is compatible with Intel Thunderbolt, when connected directly to a supporting DisplayPort over Thunderbolt I/O port. Plus, because the converter cable supports video resolutions up to 1920x1200 you can convert a DisplayPort video source to VGA without sacrificing video quality.

The MDP2VGAMM10B is backed by a 3-year StarTech.com warranty and free lifetime technical support.

Certifications, Reports and Compatibility

Applications

- Use your VGA monitor as a secondary display, connected to a Mini DisplayPort output
- Connect a Mini DisplayPort computer to a VGA projector for presentations or meetings in a boardroom or auditorium setting
- Connect your existing VGA display device (monitor, projector) to a DisplayPort output device (PC, laptop, Mac, Ultrabook)

Features

• Active Mini DisplayPort to VGA conversion



- Plug-and-Play Installation
- Supports resolutions up to 1920x1200 (WUXGA) and HDTV resolutions up to 1080p
- Compatible with Intel Thunderbolt devices that are capable of outputting a DisplayPort signal

Warranty	3 Years
Active or Passive Adapter	Active
AV Input	Mini DisplayPort - 1.2
AV Output	VGA
Audio	No
Chipset ID	Analogix - 9832
Maximum Cable Length	10.0 ft [3.0 m]
Maximum Analog Resolutions	1920x1200 / 1080p (Output)
Maximum Digital Resolutions	1920x1200 / 1080p (Input)
Audio Specifications	VGA - No Audio Support
MTBF	1,449,804 hours
Connector A	Mini-DisplayPort (20 pin)
Connector B	VGA (15 pin, High Density D-Sub)
Operating Temperature	0C to 60C (32F to 140F)
Storage Temperature	-10C to 70C (14F to 158F)
Humidity	40%-85%RH
	Active or Passive AdapterAV InputAV OutputAudioChipset IDMaximum Cable LengthMaximum Analog ResolutionsMaximum Digital ResolutionsAudio SpecificationsMTBFConnector A Connector BOperating Temperature Storage Temperature



	Cable Length	10.0 ft [3.0 m]
	Product Length	36.0 in [91.5 cm]
	Product Width	1.6 in [40 mm]
	Product Height	0.6 in [15 mm]
	Weight of Product	5.1 oz [144 g]
Packaging Information		
	Package Length	9.4 in [24 cm]
	Package Width	6.3 in [16 cm]
	Package Height	0.8 in [20 mm]
	Shipping (Package) Weight	5.3 oz [150 g]
What's in the Box	Included in Deckers	Mini Dianta Dort to VOA Adortes Coble
	Included in Package	Mini DisplayPort to VGA Adapter Cable

*Product appearance and specifications are subject to change without notice.

