

3 Port 2b 1a PCI 1394b FireWire Adapter Card with DV Editing Kit

Product ID: PCI1394B_3



The PCI1394B_3 3-Port PCI FireWire Adapter Card turns a PCI slot into 2 FireWire 800 (IEEE 1394b) ports and 1 FireWire 400 (IEEE 1394a) port - a cost-effective solution that lets you connect FireWire 800 devices, as well as older FireWire 400 devices to your desktop computer.

A versatile FireWire solution, the adapter card works in both 5v and 3.3v PCI slots and in 64-bit and 32-bit operating environments, making it easy to create a high-speed laptop digital media center, or connect demanding FireWire peripheral devices such as portable hard drives, DV camcorders, digital cameras and CD-RW/DVD-RW drives.

This high quality adapter card is designed to provide reliable FireWire 800 and FireWire 400 connections, delivering 800 Mbps and 400 Mbps data transfer rates respectively (a 64-bit PCI slot is required to achieve 800 Mbps data transfer rates).

The PCI1394B_3 is backed by a StarTech.com lifetime warranty and free lifetime technical support.

Certifications, Reports and Compatibility

Applications

- Add a high-speed FireWire port to a desktop without any FireWire ports
- Connect a digital camera to a PCI/PCI-X enabled desktop to download photos and video
- Connect a high-speed external hard drive to an PCI/PCI-X enabled system

Features

- Two FireWire 800 ports with support for data transfer rates up to 800 Mbps

- One FireWire 400 port with support for transfer rates up to 400 Mbps
- Complaint with IEEE 1394-1995, 2000, 1394b and OHCI 1.1 standards
- Compliant with PCI revision 2.2 specifications
- Compatible with 3.3V/5V, 32/64-bit PCI or PCI-X slots
- Plug-and-Play and Hot-Swap compatible
- Includes Video Editing kit: Ulead Video Studio SE and FireWire cable

Hardware

Warranty	Lifetime
Ports	3
Interface	FireWire 400 (1394a) FireWire 400 (1394a)
Bus Type	PCI / PCI-X (5 / 3.3V)
Card Type	Standard Profile
Industry Standards	PCI 2.2, OHCI, IEEE-1394B, IEEE-1394A, IEEE-1394
Chipset ID	Texas Instruments - 3AA651W

Performance

Maximum Data Transfer Rate	800 Mbps
----------------------------	----------


Connector(s)

Connector Type(s)	PCI / PCI-X (Universal 3.3 & 5V, 64-bit)
External Ports	FireWire 400 (6 pin, IEEE 1394a) FireWire 800 (9 pin, IEEE 1394b)

Software

OS Compatibility	Windows 2000, XP, Vista, 7, 8/8.1, 10, 11 Mac OS 10.2.x Linux 2.4
------------------	---

Special Notes /



Requirements

System and Cable Requirements

Unused PCI slot

The PCI1394B_3 must be installed in a 64-bit PCI slot to achieve 800 Mbps data transfer rates. In a 32-bit PCI slot, the card defaults to 400 Mbps as the data transfer speed for all attached peripherals, including FireWire 800 devices

Physical Characteristics

Color	Green
Material	Steel
Product Length	6.6 in [16.7 cm]
Product Width	0.7 in [18 mm]
Product Height	3.9 in [99 mm]
Weight of Product	3.1 oz [89 g]

Packaging Information

Package Length	8.3 in [21.2 cm]
Package Width	1.6 in [40 mm]
Package Height	5.7 in [14.4 cm]
Shipping (Package) Weight	10.2 oz [290 g]

What's in the Box

Included in Package	PCI FireWire Card
	FireWire Cable
	Software CD
	Instruction Manual

****Product appearance and specifications are subject to change without notice.***

