

Data Sheet

Fujitsu Server PRIMERGY RX2520 M5 Rack Server

Scalable rack server for essential business apps

Fujitsu offers a fantastic blend of systems, solutions and expertise to guarantee maximum productivity, efficiency and flexibility, delivering confidence and reliability. Fujitsu Server PRIMERGY systems deliver workload-optimized x86 industry standard servers for any workload and business demand. Since there is no single server solution to meet all these needs, Fujitsu offers a broad server portfolio consisting of expandable tower servers, versatile rack-mount servers, density-optimized multi-node servers as well as GPU servers purpose-built for the demands of AI and VDI. While all these systems are designed to handle multiple workloads, each server is optimized for specific use cases. Whatever the size of your business – large enterprise with multiple sites, or a small or medium-sized company with limited space and budget – with the right choice of server, your IT can become the business enabler you have always wanted it to be.

PRIMERGY RX2520 M5

The Fujitsu PRIMERGY RX2520 M5 is an efficient and scalable platform for essential business applications. As a dual-socket rack server it features the latest Intel® Xeon® Scalable Family processors with max. 20 cores fueled by up to 768 GB RAM. The system can also be equipped with the new 2nd generation processors of the Intel® Xeon® Scalable Family (CLX-R) delivering industry-leading frequencies. The PRIMERGY RX2520 delivers an especially well balanced price / performance ratio making it ideal for baseline datacenter workloads i.e. for collaboration platforms or storage-hungry applications. Its compact PRIMERGY 2U modular chassis provides storage demanding applications and services a powerful environment of up to twelve 3.5-inch or up to twenty-four 2.5-inch storage drives. Furthermore, the RX2520 M5 is prepared for individual future demands by offering further various modular options and upgrade kits for

LAN, RAID and storage. Power supply units with 96% efficiency and the enhanced iRMC S5 remote management will result in lower operational costs.



Features & Benefits

Main Features	Benefits
<p>NEW 2ND GEN INTEL® XEON® SCALABLE PROCESSORS</p> <ul style="list-style-type: none"> ■ New Intel Xeon Scalable processor SKUs deliver additional customer value with increased performance and industry leading frequency (up to 3.9 GHz base and up to 44% more processor cache). <p>FLEXIBLE AND SCALABLE PLATFORM</p> <ul style="list-style-type: none"> ■ Huge numbers of storage drives in various base units with up to 12x 3.5-inch or 24x 2.5-inch storage drives are available. M.2 device support, the modular concept for the base unit as well as a choice for optional LAN controller, RAID controller and power supplies as well as built-in backup devices such as LTO drives are configurable for this server. <p>PROTECT YOUR COMPANY WITH SECURE SERVERS</p> <ul style="list-style-type: none"> ■ PRIMERGY servers are equipped with beneficial features to protect against, detect and recover from security breaches (UEFI Secure Boot, TPM 2.0, signed firmware updates, agent-free device management, secure authorization and authentication, alerting and logging, secure Out of Band Management with iRMC S5, ...). <p>INFRASTRUCTURE MANAGEMENT</p> <ul style="list-style-type: none"> ■ ISM is available with two licensing options: (1) ISM Advanced is the fully featured licensed version of ISM that provides comprehensive infrastructure management capabilities across datacenter. (2) ISM Essential provides a quick start to infrastructure management with essential monitoring and update functions. 	<ul style="list-style-type: none"> ■ These new platforms leverage high-performance compute cores, built-in acceleration, advanced security and the Intel hardware and software portfolio to propel network, cloud and enterprise customers into the data-centric future. ■ The server is a scalable platform to best meet increasing individual demand optimized to suit serverized storage scenarios or storage demanding applications. Due to upgrade kits and the modular platform, just grow over time within the same system and utilize to the best over the entire lifecycle. ■ PRIMERGY servers come with a wide variety of such robust security features and combine these capabilities with the best quality and efficiency, and more agility in daily operations helps to turn IT into a business advantage faster. ■ Converged data center management that provides organizations centralized control over the entire infrastructure that includes servers, storage, networking, cloud management software as well as power and cooling using a single user interface.

Technical details

PRIMERGY RX2520 M5

Base unit	PRIMERGY RX2520 M5 SFF	PRIMERGY RX2520 M5 SFF	PRIMERGY RX2520 M5 SFF	PRIMERGY RX2520 M5 LFF	PRIMERGY RX2520 M5 LFF
Housing types	Rack	Rack	Rack	Rack	Rack
Storage drive architecture	8x 2.5-inch SAS/SATA/PCIe	16x 2.5-inch SAS/SATA/PCIe	24x 2.5-inch SAS/SATA/PCIe	4x 3.5-inch SAS/SATA	12x 3.5-inch SAS/SATA
Power supply	Hot-plug	Hot-plug	Hot-plug	Hot-plug	Hot-plug
Product Type	Dual Socket Rack Server	Dual Socket Rack Server	Dual Socket Rack Server	Dual Socket Rack Server	Dual Socket Rack Server

Mainboard

Mainboard type	D3386-B
Chipset	Intel® C624
Processor quantity and type	1 - 2 x Intel® Xeon® Bronze 3xxx processor / Intel® Xeon® Silver 4xxx processor / Intel® Xeon® Gold 5xxx processor

Mainboard type

Processor quantity and type	1 - 2	1 - 2	1 - 2	1 - 2	1 - 2
-----------------------------	-------	-------	-------	-------	-------

Intel® Xeon® Bronze Processor

Intel® Xeon® Bronze 3204 (6C, 1.90 GHz, TLC: 8.25 MB, Turbo: 1.90 GHz, 9.6 GT/s, Mem bus: 2,133 MHz, 85 W, AVX Base 1.50 GHz, AVX Turbo 1.50 GHz)
Intel® Xeon® Bronze 3206R (8C, 1.90 GHz, TLC: 11 MB, Turbo: 1.90 GHz, 9.6 GT/s, Mem bus: 2,133 MHz, 85 W, AVX Base 1.80 GHz, AVX Turbo 1.80 GHz)

Intel® Xeon® Silver Processor

Intel® Xeon® Silver 4208 (8C, 2.10 GHz, TLC: 11 MB, Turbo: 2.50 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 85 W, AVX Base 1.60 GHz, AVX Turbo 2.00 GHz)
Intel® Xeon® Silver 4210 (10C, 2.20 GHz, TLC: 13.75 MB, Turbo: 2.70 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 85 W, AVX Base 1.90 GHz, AVX Turbo 2.30 GHz)
Intel® Xeon® Silver 4210R (10C, 2.40 GHz, TLC: 13.75 MB, Turbo: 2.90 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 100 W, AVX Base 1.90 GHz, AVX Turbo 2.40 GHz)
Intel® Xeon® Silver 4214 (12C, 2.20 GHz, TLC: 16.5 MB, Turbo: 2.70 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 85 W, AVX Base 1.80 GHz, AVX Turbo 2.40 GHz)
Intel® Xeon® Silver 4214R (12C, 2.40 GHz, TLC: 16.5 MB, Turbo: 3.00 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 100 W, AVX Base 2.10 GHz, AVX Turbo 2.70 GHz)
Intel® Xeon® Silver 4214Y (12C, 2.20 GHz, TLC: 16.5 MB, Turbo: 2.70 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 85 W, AVX Base 1.80 GHz, AVX Turbo 2.40 GHz)
Intel® Xeon® Silver 4215 (8C, 2.50 GHz, TLC: 11 MB, Turbo: 3.00 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 85 W, AVX Base 2.00 GHz, AVX Turbo 2.60 GHz)
Intel® Xeon® Silver 4215R (8C, 3.20 GHz, TLC: 11 MB, Turbo: 3.60 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 130 W, AVX Base 2.00 GHz, AVX Turbo 2.60 GHz)
Intel® Xeon® Silver 4216 (16C, 2.10 GHz, TLC: 22 MB, Turbo: 2.70 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 100 W, AVX Base 1.40 GHz, AVX Turbo 2.30 GHz)

Intel® Xeon® Gold Processor

Intel® Xeon® Gold 5215 (10C, 2.50 GHz, TLC: 13.75 MB, Turbo: 3.00 GHz, 10.4 GT/s, Mem bus: 2,666 MHz, 85 W, AVX Base 2.00 GHz, AVX Turbo 2.60 GHz)
Intel® Xeon® Gold 5217 (8C, 3.00 GHz, TLC: 11 MB, Turbo: 3.40 GHz, 10.4 GT/s, Mem bus: 2,666 MHz, 115 W, AVX Base 2.50 GHz, AVX Turbo 3.00 GHz)
Intel® Xeon® Gold 5218 (16C, 2.30 GHz, TLC: 22 MB, Turbo: 2.80 GHz, 10.4 GT/s, Mem bus: 2,666 MHz, 125 W, AVX Base 1.80 GHz, AVX Turbo 2.30 GHz)
Intel® Xeon® Gold 5218B (16C, 2.30 GHz, TLC: 22 MB, Turbo: 2.80 GHz, 10.4 GT/s, Mem bus: 2,666 MHz, 125 W, AVX Base 1.80 GHz, AVX Turbo 2.30 GHz)
Intel® Xeon® Gold 5218R (20C, 2.10 GHz, TLC: 27.5 MB, Turbo: 2.90 GHz, 10.4 GT/s, Mem bus: 2,666 MHz, 125 W, AVX Base 1.70 GHz, AVX Turbo 2.70 GHz)
Intel® Xeon® Gold 5220 (18C, 2.20 GHz, TLC: 24.75 MB, Turbo: 2.70 GHz, 10.4 GT/s, Mem bus: 2,666 MHz, 125 W, AVX Base 1.80 GHz, AVX Turbo 2.50 GHz)
Intel® Xeon® Gold 5222 (4C, 3.80 GHz, TLC: 16.5 MB, Turbo: 3.90 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 105 W, AVX Base 3.80 GHz, AVX Turbo 3.80 GHz)

Processor notes

configurable with up to max. 105W and 14 cores

Memory slots	12 (6 DIMMs per CPU, 6 channels with 1 DIMM per channel)				
Memory slot type	DIMM (DDR4)				
Memory capacity (min. - max.)	8 GB - 768 GB				
Memory protection	Advanced ECC Memory Scrubbing SDDC				
Memory notes	Memory Mirroring Mode with identical modules in both channel pairs of a bank (4 or 6 modules per bank) per CPU. Rank Sparing Mode with minimum of 2 modules single ranked (1R) or dual ranked (2R) or 1 module quad ranked (4R) per CPU.				
Standard memory modules	8 GB (1 module(s) 8 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 1Rx8 16 GB (1 module(s) 16 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 1Rx4 16 GB (1 module(s) 16 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 2Rx8 32 GB (1 module(s) 32 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 2Rx4 64 GB (1 module(s) 64 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 2Rx4				
Interfaces					
USB 2.x ports	1 x USB 2.0 internal for backup devices				
USB 3.x ports	7 x USB 3.0 (2x front, 4x rear, 1x internal type A)				
Graphics (15-pin)	1 x VGA rear				
Serial 1 (9-pin)	1 x serial RS-232-C, optional				
LAN / Ethernet	2 x Gbit/s Ethernet (RJ45 based on Intel® X722)				
Management LAN (RJ45)	1 x dedicated management LAN port for iRMC S5 (10/100/1000 Mbit/s) Management LAN traffic can be switched to shared onboard Gbit LAN port				
Onboard or integrated Controller					
RAID controller	All hardware storage controller options are described under Components				
SATA Controller	Intel® C624, 1 x SATA channel for ODD				
LAN Controller	2 x 1 Gbit/s onboard PXE-Boot via LAN from PXE server, iSCSI boot (also diskless)				
Remote management controller	IPMI 2.0 compatible Integrated Remote Management Controller (iRMC S5, 512 MB attached memory incl. graphics controller)				
Trusted Platform Module (TPM)	Infineon / TPM 1.2 or TPM 2.0 module; TCG compliant (option)				
Slots					
PCI-Express 4.0 x16	1 x (190 mm) low profile				
PCI-Express 3.0 x8	3 x Low profile				
PCI-Express 3.0 x16	3 x Low profile				
Slot Notes	Important: The number of PCIe slots depends on the number of CPUs: 3x PCIe x8 Gen 3 with CPU1 1x PCIe x16 Gen 3 with CPU1 2x PCIe x16 Gen 3 with CPU2				
Drive bays					
Storage drive bays	2.5-inch base units (max. 24 x 2.5) or 3.5-inch base units (max. 12 x 3.5)				
Accessible drive bays	1 x 5.25/0.5-inch for ODD 1 x 5.25/1.6-inch for backup devices				
Notes accessible drives	All possible options described in relevant system configurator.				
Drive bays (Base unit specific)					
Storage drive bays	12 x 2.5-inch hot-plug SAS/SATA	16 x 2.5-inch hot-plug SAS/SATA	24 x 2.5-inch hot-plug SAS/SATA	4 x 3.5-inch hot-plug SAS/SATA	12 x 3.5-inch hot-plug SAS/SATA
Storage drive bay configuration		SAS expander not required with PRAID EP5xxi	not expandable, incl. SAS expander	optionally expandable to 8x 3.5" with SAS expander	not expandable, incl. SAS expander
Accessible drive bays	1 x 5.25/1.6-inch for 1 x backup drive or 1 x ODD	1 x 5.25/1.6-inch for 1 x backup drive or 1 x ODD		1 x 5.25/1.6-inch for 1 x backup drive or 1 x ODD	
Optional accessible drives	1x optical drive, 1x backup drive	1x optical drive, 1x backup drive		1x optical disk drive	

Fan Configuration

Number of fans	4
Fan configuration	redundant, non hot-plug
Fan notes	expandable with up to 3 double-fan modules; depending on configuration

Operating panel

Operating buttons	On/off switch Reset button NMI button ID button
Status LEDs	System status (orange / yellow) Identification (blue) Hard disks access (green) Power (amber / green) At system rear side: System status (orange / yellow) Identification (blue) LAN connection (green) LAN speed (green / yellow)

BIOS

BIOS features	ROM based setup utility Recovery BIOS BIOS settings save and restore Local BIOS update from USB device Online update tools for main Linux versions Local and remote update via ServerView Update Manager SMBIOS V2.4 Remote PXE boot support Remote iSCSI boot support Cryptographically Signed BIOS Firmware Update HTTP and HTTPS Boot PCIe Bifurcation configurable
---------------	---

Operating Systems and Virtualization Software

Certified or supported operating systems and virtualization software	Windows Server 2019 Datacenter Windows Server 2019 Standard Windows Server 2019 Essentials Windows Server Datacenter, version 1809 Windows Server Standard, version 1809 Hyper-V Server 2016 Windows Server 2016 Datacenter Windows Server 2016 Standard Windows Server 2016 Essentials Windows Storage Server 2016 Standard Windows Server Datacenter, version 1709 VMware vSphere™ 7.0 VMware vSphere™ 6.7 VMware vSphere™ 6.5 SUSE® Linux Enterprise Server 12 Red Hat® Enterprise Linux 8 Red Hat® Enterprise Linux 7 Univention Corporate Server 4
Operating system release link	http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473
Operating system notes	Support of other Linux derivatives on demand

Infrastructure and Server Management

DC Infrastructure Management	Infrastructure Manager (ISM) Essential Edition Advanced Edition
------------------------------	---

Infrastructure and Server Management

Server Management	Infrastructure Manager (ISM) Essential Edition Advanced Edition ServerView Suite
Management notes	For further information regarding ISM and ServerView Suite see dedicated data sheets.
Manageability link	http://docs.ts.fujitsu.com/dl.aspx?id=9e92297a-16fb-4c69-8559-e38e7b42fee6

Dimensions / Weight

Rack (W x D x H)	482.4 mm (Bezel) / 445mm (Body) x 770 x 86.6 mm
Mounting Depth Rack	740 mm
Height Unit Rack	2 U
19" rackmount	Yes
Weight	up to 25 kg
Weight notes	Actual weight may vary depending on configuration
Rack integration kit	Rack integration kit as option

Environment

Operating ambient temperature	5 - 45 °C (41 - 113 °F)
Operating temperature note	Cool-safe® Advanced Thermal Design (above 35 °C or below 10 °C) depending on configuration. Please use the Fujitsu WebArchitect (www.fujitsu.com/configurator/public) to get detailed information on the corresponding configurations.
Operating relative humidity	10 - 85 % (non condensing)
Operating environment	FTS 04230 – Guideline for Data Center (installation specification)
Operating environment link	http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe
Noise emission	Measured according to ISO 7779 and declared according to ISO 9296
Sound pressure (LpAm)	Minimum noise : 34 dB(A) (idle) / 34 dB(A) (operating) Typical noise : 36 dB(A) (idle) / 36 dB(A) (operating)
Sound power (LWA; 1B = 10dB)	Minimum noise : 5.76 B (idle) / 5.76 B (operating) Typical noise : 6.1 B (idle) / 6.1 B (operating)
Noise notes	Noise emissions depends on operation modes, system configuration and ambient temperature.

Electrical values

Power supply configuration	1x non hot-plug power supply or 2x hot-plug power supply for redundancy
Hot-plug power supply redundancy	Optional
Active power (max. configuration)	643 W
Apparent power (max. configuration)	600 VA
Heat emission (max. configuration)	2314.8 kJ/h (2194.0 BTU/h)
Rated current max.	5.5 A (100 V) / 2.5 A (240 V)
Active power note	To estimate the power consumption of different configurations use the Fujitsu Product Configurator: www.fujitsu.com/configurator/public
Power supply	450W hot-plug, 94% (Platinum efficiency), 100-240V, 50 / 60Hz 800W hot-plug, 94% (Platinum efficiency), 100-240V, 50 / 60Hz 800W hot-plug, 92% (equivalent to Gold efficiency) –48V DC 800W hot-plug, 96% (Titanium efficiency), 200-240V, 50 / 60Hz
Power supply notes	Power Safeguard adapts system performance in case the power requirements exceeds supply limits. !96% Titanium Power supply unit is only released for 200-240V

Compliance

Product	PRIMERGY RX2520 M5
Model	PR300D
Global	CB RoHS (Substance limitations in accordance with global RoHS regulations) WEEE (Waste electrical and electronic equipment)
Germany	GS
Europe	CE
USA/Canada	CSAc/us FCC Class A ICES-003 / NMB-003 Class A

Compliance	
Japan	VCCI:V3 Class A + JIS 61000-3-2
Russia	EAC
South Korea	KC
China	CCC (planned)
Australia/New Zealand	RCM
Taiwan	BSMI
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
Compliance notes	<p>There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request.</p> <p>* Warning:</p> <p>This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.</p>

Components

Backup Drives	LTO7HH Ultrium, 2,500 GB, 300 MB/s, half height, SAS 6Gb/s
	LTO7HH Ultrium, 300 MB/s, half height, SAS 6Gb/s
	RDX Drive, 320 GB, 500 GB, 1 TB , 25 MB/s, half height, USB 3.0
Optical drives	Blu-ray Disc™ Triple Writer, (6x BD-RW, 8x DVD, 24x CD), ultraslim, SATA I
	DVD Super Multi ultra slim , (8x DVD; 24x CD), ultraslim, SATA I
Hard disk drives	HDD SATA, 6 Gb/s, 18 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 16 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 14 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 12 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 8 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 6 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 4 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical
	HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512e, hot-plug, 2.5-inch, business critical
	HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical
	HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512e, hot-plug, 2.5-inch, business critical

Hard disk drives

HDD SAS, 12 Gb/s, 900 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 900 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 900 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 900 GB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 300 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 300 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 18 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 18 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 16 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 16 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 14 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 14 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 12 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 12 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 10 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 8 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 6 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 6 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 2.4 TB, 10,000 rpm, 512e, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 2.4 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 2.4 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 2 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical
HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, 512n, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 1 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical

PCIe SSD & SATA DOM SSD	PCIe-SSD SFF, 6.4 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD (Drive Writes Per Day for 5 years)
	PCIe-SSD SFF, 4 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD (Drive Writes Per Day for 5 years)
	PCIe-SSD SFF, 3.2 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD (Drive Writes Per Day for 5 years)
	PCIe-SSD SFF, 2 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD (Drive Writes Per Day for 5 years)
	PCIe-SSD SFF, 1.6 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD (Drive Writes Per Day for 5 years)
	PCIe-SSD SFF, 1 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD (Drive Writes Per Day for 5 years)
SCSI / SAS Controller	Broadcom® PSAS CP503i LP SAS Ctrl. 12 Gbit/s 8 ports int. PCIe 3.0 x8
RAID Controller	pre-configured RAID6 Array,
	pre-configured RAID6+HS Array,
	pre-configured RAID5 Array,
	pre-configured RAID5+HS Array,
	pre-configured RAID1 Array,
	pre-configured RAID1+HS Array,
	pre-configured RAID1+0 Array,
	pre-configured RAID1+0+HS Array,
	pre-configured RAID0 Array,
	Fujitsu PRAID EP580i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 8 Gbit/s, 8 Gbit/s 16 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 8 GB, Optional FBU based on LSI SAS3516
Fujitsu PRAID EP540i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 8 Gbit/s, 8 Gbit/s 16 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 4 GB, Optional FBU based on LSI SAS3516	
Fujitsu PRAID EP540e LP, RAID 5/6 Ctrl., SAS 12 Gbit/s, 8 ports ext. RAID level: 0, 1, 10, 5, 50, 6, 60, 4 GB, Optional FBU based on LSI SAS3516	
Fujitsu PRAID EP520i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 8 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 2 GB, Optional FBU based on LSI SAS3516	
Fujitsu PRAID CP400i, RAID Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 1E, 10, 5, 50, No FBU support	
Broadcom® PSAS CP503i LP, SAS Ctrl., SAS/SATA 12 Gbit/s, 8 ports int.	
Broadcom® PSAS CP500e LP, SAS Ctrl., SAS/SATA 12 Gbit/s, 8 ports ext.	
Broadcom® PRAID CP500i LP, RAID Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, No FBU support	
Fibre Channel controller	Fibre Channel Host Bus Adapter 1 x 32 Gbit/s Cavium QLE2740 MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 32 Gbit/s Cavium QLE2742 MMF LC-style
	Fibre Channel Host Bus Adapter 1 x 32 Gbit/s Emulex LPe32000-M6-F MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 32 Gbit/s Emulex LPe32002-M6-F MMF LC-style
	Fibre Channel Host Bus Adapter 1 x 16 Gbit/s Qlogic QLE2690 LC-style
	Fibre Channel Host Bus Adapter 2 x 16 Gbit/s Qlogic QLE2692 LC-style
	Fibre Channel Host Bus Adapter 1 x 16 Gbit/s Emulex LPe31000-M6-F MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 16 Gbit/s Emulex LPe31002-M6-F MMF LC-style
Communication, Network	Converged Network Adapter 2 x 10 Gbit/s / 25 Gbit/s PCIe 3.0 x8 SFP28 (Cavium)
	Ethernet Ctrl. 1 x 100 Gbit/s PCIe 3.0 x16 QSFP28 (Cavium)
	Ethernet Ctrl. 2 x 10 Gbit/s ; 1 Gbit/s PCIe 3.0 x8 RJ45 (Cavium)
	Ethernet Ctrl. 2 x 10 Gbit/s ; 1 Gbit/s PCIe 3.0 x8 SFP+ (Cavium)
	Ethernet Ctrl. 2 x 10 Gbit/s / 25 Gbit/s PCIe 3.0 x8 SFP28 (Cavium)
	Ethernet Ctrl. 4 x 10 Gbit/s ; 1 Gbit/s PCIe 3.0 x8 RJ45 (Intel®)
Graphics add on cards	NVIDIA® Quadro® P400 , 2 GB, N/A, PCIe x16, 3 x miniDP
Rack infrastructure	Rackmount kit full extraction (820mm), tool less mounting, length variable 559-914mm
	Rack Mount Kit
	Cable Arm 2U for PRIMECENTER- and 3rd-party racks
Warranty	
Warranty period	3 years
Warranty type	Onsite warranty

Warranty

Warranty Terms & Conditions www.fujitsu.com/support

Product Support Services - the perfect extension

Support Pack Options Globally available in major metropolitan areas:
9x5, Next Business Day Onsite Response Time
9x5, 4h Onsite Response Time (depending on country)
24x7, 4h Onsite Response Time (depending on country)

Recommended Service 24x7, Onsite Response Time: 4h - For locations outside of EMEA please contact your local Fujitsu partner.

Service Lifecycle 5 years after end of product life

Service Weblink <http://www.fujitsu.com/emeia/products/product-support-services/>

More information

Fujitsu products, solutions & services

In addition to Fujitsu Server PRIMERGY RX2520 M5, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Built on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offerings. This allows customers to select from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu Server PRIMERGY RX2520 M5, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/primergy

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>
Copyright 2022 Fujitsu LIMITED

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.