

External Docking Station for 2.5in or 3.5in SATA III 6Gbps Hard Drives - eSATA or USB 3.0 with UASP

Product ID: SDOCKU33EF



This USB 3.0 and eSATA docking station makes it easy for you to connect and swap your 2.5in or 3.5in SATA hard drives (HDD) and solid-state drives (SSD). The docking station also has a built-in fan that keeps your drives running at an optimal temperature for peak performance and longer drive lifespan.

With support for either USB 3.0 or eSATA host connections, this versatile drive dock gives you the freedom to connect to your computer through either port. Because USB is available on virtually any computer, you can rest assured that this docking station will work with your desktop or laptop. Plus, the added benefit of eSATA ensures you can achieve SATA 6 Gpbs performance on computers with an available eSATA port.

To ensure all your drives are supported, the docking station features a sleek slot-loading design that supports both 2.5in and 3.5in drives. The docking station has also been rigorously tested for support with large capacity drives (tested up to 6TB).

You can extend the compatibility of this dock even further by adding IDE support using our SATA to IDE Hard Drive Adapter (SAT2IDEADP), which allows for easy insertion of any 2.5 or 3.5in IDE hard drive into a SATA hard drive dock.

For optimal performance, the docking station has a built-in 80mm fan that helps keep your drives running cooler. The fan offers variable speed control which enables you to make adjustments on the fly, in order to reduce power consumption and noise when your drives aren't being accessed. The HDD dock will also power down your SATA drives after a period of inactivity (USB mode only) or when the computer is turned off, to help reduce power consumption and noise when not being accessed.

To save you time, this docking station is loaded with high-performance features on both interface connections.

For the fastest possible performance, this dock supports full SATA III bandwidth of 6 Gbps when connected through eSATA, ensuring you can get the most out of your solid-state drives.

With USB 3.0 the dock ensures high-bandwidth transfer speeds up to 5 Gbps. The USB host interface connection also supports UASP, which delivers performance up to 70% faster than conventional USB 3.0 when paired with a



compatible host controller. UASP is supported in Windows 8, Mac OSX (10.8 or above), and Linux. In testing, UASP performs with a 70% faster read speed and 40% faster write speed over traditional USB 3.0 at peak performance.

At the same peak in testing UASP also shows an 80% reduction in required processor resources.

Testing results were obtained using an Intel Ivy Bridge system, a UASP-enabled StarTech.com enclosure, and a SATA III solid state drive.

The SDOCKU33EF is backed by a 2-year StarTech.com warranty and free lifetime technical support.

Certifications, Reports and Compatibility

Applications

- Quickly access drives for data recovery or retrieval
- Backup data to an external drive for data archiving
- Test or benchmark different hard drives while easily swapping between them
- Quickly access drives for imaging

Features

- Optimal performance with SATA 6 Gbps and USB 3.0 with UASP
- Maximum compatibility with eSATA or USB 3.0 interface options
- Keep your drives running cool using the built-in fan with variable speed control
- Supports 2.5in and 3.5in form factor SATA hard drives (HDD) and solid state drives (SSD)
- Compatible with USB 3.0/2.0/1.1 (5 Gbps / 480 Mbps / 1.5 Mbps)
- Compatible with SATA revision I/II/III (1.5/3.0/6.0 Gbps) drives
- Plug-and-play and hot-swap compatible

Hardware			
	Warranty	2 Years	
	Fan(s)	Yes	
	Fans	80 mm	
	Interface	USB 3.0 & eSATA	



Bus Type USB 3.0 & eSATA

Number of Drives 1

Drive Size 2.5in & 3.5in

Compatible Drive Types SATA

Drive Installation Removable

Chipset ID JMicron - JMS561

Performance

Maximum Data Transfer

eSATA - 6 Gbps

Rate

USB 3.0 - 5 Gbps

Type and Rate USB 3.0 - 5 Gbit/s

UASP Support Yes

4Kn Support Yes

Type and Rate SATA III (6 Gbps)

Max Drive Capacity Currently tested with up to 6TB 7200 RPM 3.5" hard drives and

2TB 7200 RPM 2.5" hard drives

Hot Swap Capability Yes

Connector(s)

Drive Connectors SATA Data & Power Combo (7+15 pin)

Host Connectors eSATA (7 pin, Data)

USB Type-B (9 pin) USB 3.0

Other Interface(s) USB Type-A (9 pin) USB 3.0 (5 Gbps)

USB Type-A (4 pin) USB 2.0

eSATA (7 pin, Data)

Software

OS Compatibility OS independent; No software or drivers required

Indicators

LED Indicators Drive Power/Activity



Power

Power

Power Source AC Adapter Included

Input Voltage 100 - 240 AC

Input Current 0.8 A

Output Voltage 12V DC

Output Current 2 A

Center Tip Polarity Positive

Plug Type M

Power Consumption (In

Watts)

Environmental

Operating Temperature 5C to 80C (41F to 176F)

24

Storage Temperature -40C to 70C (-40F to 158F)

Humidity 8~90% RH

Physical Characteristics

Color Black

Material Plastic

Product Length 5.0 in [12.6 cm]

Product Width 3.7 in [95.0 mm]

Product Height 5.3 in [13.4 cm]

Weight of Product 16.6 oz [470.0 g]

Packaging Information

Package Length 4.8 in [12.1 cm]

Package Width 7.4 in [18.7 cm]

Package Height 8.3 in [21.1 cm]



Shipping (Package)	
Weight	

33.8 oz [957.0 g]

What's in the Box

Included in Package eSATA / USB 3.0 SATA HDD DOCK

1m USB 3.0 Cable

1m eSATA Cable

Universal Power Adapter (NA/UK/EU/AUS)

Instruction Manual

^{*}Product appearance and specifications are subject to change without notice.