

Technical Specifications

APC Rack PDU 9000 Switched, ZeroU, 5.7kW, 200/208V, (21) C13/C15 & (3) C19/C21 | APDU9961 | Downloaded on 03/01/2021 (EST)



APC Rack PDU 9000 Switched, ZeroU, 5.7kW, 200/208V, (21) C13/C15 & (3) C19/C21

APDU9961

Call for More Information 0800 2799254

- Includes: Installation guide, Rack mounting brackets, Safety guide

Output

Nominal Output Voltage	208V
Overload Protection	No
Maximum Total Current Draw	20
Output Connections	(21) C13/C15 (3) C19/C21

Input

Nominal Input Voltage	208V 3PH
Input frequency	50/60 Hz
Input Connections	NEMA L21-20P
Cord Length	1.8meters
Number of Power Cords	1
Load Capacity	5700VA
Maximum Input Current	20A
Maximum Line Current	20A
Regulatory Derated Input Current (North America)	16A

Physical

Maximum Height	1792MM, 179.2CM
Maximum Width	55MM, 5.5CM
Maximum Depth	46MM, 4.6CM
Net Weight	6.91KG

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Physical	
Shipping weight	8.82KG
Shipping Height	2002MM, 200.2CM
Shipping Width	165MM, 16.5CM
Shipping Depth	114MM, 11.4CM
Color	Black
Units per Pallet	48.0

Environmental	
Operating Temperature	-5 - 60 °C
Operating Relative Humidity	5 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-25 - 65 °C
Storage Elevation	0 - 15240meters

Conformance	
Approvals	CUL listed, FCC part 15 class A, IEC 62368-1
Standard warranty	3 years repair or replace

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.