

4 Port Gigabit Power over Ethernet PCIe Network Card - PSE / PoE PCI Express NIC

Product ID: ST4000PEXPSE



The ST4000PEXPSE 4-Port PoE NIC lets you add four Gigabit Power over Ethernet ports through a single PCI Express slot. Each port can provide up to 25.5W of power, combining network data and power over a single Ethernet cable for reduced cable clutter and added convenience for remote PoE devices.

The PCI express PoE card supports the IEEE 802.3at (Type 1 and 2) standard for Power Sourcing Equipment (PSE), and can deliver up to 48V DC power to compliant Powered Devices (PD). This eliminates the need for a separate power source and data connection for PoE devices such as IP cameras, IP phones or wireless access points.

Suitable for any standard profile PCIe-enabled client, server or workstation, the PoE network card supports features such as Jumbo Frames (up to 9KB), VLAN tagging and Wake on LAN (WoL).

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility

Applications

• Create a host computer for networked security cameras situated in remote areas, where standard power connection is not possible

• Install PoE-powered Wireless Access Points (WAP) or repeaters in industrial, warehousing or business environments

• Enable remote installation of touchscreens or information kiosks

Features



- Four 10/100/1000 Mbps compatible PoE RJ45 ports
- Fully compliant with IEEE 802.3at (Type 1 & 2) Power over Ethernet standards
- Power Sourcing Equipment (PSE) supports up to 48V, 25.5 Watts max. output per port
- Built-in SATA and LP4 Molex power connector
- Up to 9K Jumbo Frame support
- Wake-on-LAN (Remote Wake-up) support
- Supports Pair Swap, Polarity and Skew Correction

| Hardware | | |
|-------------|-------------------------------|--|
| | Warranty | 2 Years |
| | Ports | 4 |
| | Interface | RJ45 (Gigabit Ethernet) |
| | Bus Type | PCI Express |
| | Card Type | Standard Profile |
| | Port Style | Integrated on Card |
| | Industry Standards | IEEE 802.3at, 802.3af, 802.3, 802.3u, 802.3ab, 802.3az Draft 2.2 Energy-Efficient Ethernet (EEE), 802.1q VLAN tagging, 802.1p Layer 2 Priority Encoding and 802.3x Full Duplex Flow Control |
| | Chipset ID | Realtek - RTL8111E |
| Performance | Maximum Data Transfer Rate | 2000 Mbps (Full-duplex) |
| | Buffer Size | 48 KB |
| | Compatible Networks | 10/100/1000 Mbps |
| | Auto MDIX | Yes |
| | Full Duplex Support | Yes |
| | Jumbo Frame Support | 9K max. |
| | Promiscuous Mode | Yes |



| Connector(s) | | |
|---------------------------------|----------------------------------|--|
| | Connector Type(s) | PCI Express x4 |
| | Internal Ports | LP4 (4 pin; Large Drive Power) |
| | | SATA Power (15 pin) |
| | External Ports | RJ-45 |
| Software | | |
| | OS Compatibility | Windows 2000, XP, Vista, 7, 8, 8.1, 10, 11 |
| | | Windows Server 2003, 2008 R2, 2012, 2012 R2, 2016, 2019 |
| | | Linux 2.4.x to 4.11.x <i>LTS Versions Only</i> |
| Special Notes / Requirements | | |
| | Patents and Licenses | The following patents are licensed for this product. This list might not be all inclusive. |
| | | United States Patent No. 5,406,260 (expired) |
| | | •United States Patent No. 6,650,622 |
| | | •United States Patent No. 7,457,250 |
| | | •United States Patent No. 8,155,012 |
| | | •United States Patent No. 8,902,760 |
| | | •United States Patent No. 8,942,107 |
| | | •United States Patent No. 9,019,838 |
| | | •United States Patent No. 9,049,019 |
| | | •United States Patent Application No. 14/695,456 |
| | | •United States Patent Application No. 14/726,940 |
| | System and Cable Requirements | Available full height (standard profile) PCI Express expansion slot |
| | | Available LP4 Molex or SATA power connector |
| Indicators | | |
| | LED Indicators | Link/ Activity (green) |
| | | PoE Active (yellow) |
| Power | Output Voltage | 48 DC |
| | | |



| Environmental | | |
|-----------------------------|------------------------------|----------------------------|
| | Operating Temperature | 0C to 55C (32F to 131F) |
| | Storage Temperature | -40C to 75C (-40F to 158F) |
| | Humidity | 10~90% RH (Non-condensing) |
| Physical Characteristics | | |
| | Color | Yellow |
| | Material | Steel |
| | Product Length | 9.6 in [24.3 cm] |
| | Product Width | 0.7 in [18.0 mm] |
| | Product Height | 4.7 in [12.0 cm] |
| | Weight of Product | 3.6 oz [102.0 g] |
| Packaging Information | | |
| | Package Length | 11.7 in [29.6 cm] |
| | Package Width | 7.4 in [18.8 cm] |
| | Package Height | 2.6 in [66.0 mm] |
| | Shipping (Package) Weight | 15.1 oz [428.0 g] |
| What's in the Box | | |
| | Included in Package | PCI Express Network Card |
| | | Driver CD |
| | | Instruction Manual |
| | | |

*Product appearance and specifications are subject to change without notice.