

6 Port USB 3.0 / USB 2.0 Combo Hub with 2A Charging Port – 2x USB 3.0 & 4x USB 2.0

Product ID: ST7320USBC



The ST7320USBC 6-Port USB 3.0/2.0 Combo Hub features a special high-output dedicated charging port which enables you to charge USB devices by providing up to 2A of power, or it can add 2x USB 3.0 and 4x USB 2.0 ports to a computer through a single USB 3.0 host connection.

The hub includes an external power adapter, which when connected enables charging some portable electronic devices (e.g. an iPhone or other Smartphone), even without a USB connection to a host computer.

Offering a unique design that features USB ports along 3 sides of the hub, as well as a combination of USB 2.0 and 3.0 ports, this versatile and flexible USB hub is ideal for both laptop and desktop computers.

The ST7320USBC USB 3.0/2.0 hub is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility

Applications

- Add multiple USB 3.0 and USB 2.0 to a computer system to support more device connections
- Charge a Smartphone
- Charging high-powered portable devices (such as tablets) which require special high output USB ports for charging
- Make USB ports that are hard to access more accessible, by being positioning the hub in a convenient location (within cable reach)
- Extend the range of a USB device by having the hub act as a mid-point repeater



Features

- 2x USB 3.0 and 4x USB 2.0 ports that can be all accessed simultaneously
- 2 Amp high output USB Dedicated Charging Port (DCP)
- Includes 20 watt power adapter and host USB 3.0 cable
- Universal, multi-platform compatible, with no additional drivers or software required
- SuperSpeed USB 3.0 compliant host interface, with support for up to 5 Gbps of data bandwidth

Warranty2 YearsUSB-C Device Port(s)NoUSB-C Host ConnectionNoFast-Charge Port(s)YesPorts7InterfaceUSB 3.0Bus TypeUSB 3.0Chipset IDVIA/VLI - VL813PerformanceType and RateExternal PortsUSB 3.0-4.8 Gbit/s USB 2.0-480 Mbit/sConnector(s)External PortsExternal PortsUSB Type-A (9 pin) USB 3.0 (5 Gbps) USB Type-A (4 pin) USB 3.0			
USB-C Device Port(s)NoUSB-C Host ConnectionNoFast-Charge Port(s)YesPorts7InterfaceUSB 3.0Bus TypeUSB 3.0Chipset IDVIA/VLI - VL813PerformanceType and RateUSB 3.0 - 4.8 Gbit/s USB 2.0 - 480 Mbit/sConnector(s)External PortsSoftwareOS CompatibilityOS CompatibilityOS Independent	Hardware		
USB-C Host ConnectionNoFast-Charge Port(s)YesPorts7InterfaceUSB 3.0Bus TypeUSB 3.0USB 3.0USB 3.0Chipset IDVIA/VLI - VL813PerformanceType and RateUSB 2.0 - 480 Mbit/sConnector(s)External PortsExternal PortsUSB Type-A (9 pin) USB 3.0 (5 Gbps)USB Type-A (4 pin) USB 3.0SoftwareOS CompatibilityOS CompatibilityOS Independent		Warranty	2 Years
Fast-Charge Port(s)YesPorts7InterfaceUSB 3.0Bus TypeUSB 3.0USB 3.0USB 3.0Chipset IDVIA/VLI - VL813PerformanceType and RateUSB 2.0 - 4.8 Gbit/s USB 2.0 - 480 Mbit/sConnector(s)External PortsExternal PortsUSB Type-A (9 pin) USB 3.0 (5 Gbps) USB Type-B (9 pin) USB 3.0 (5 Gbps) USB Type-A (4 pin) USB 2.0SoftwareOS CompatibilityOS CompatibilityOS Independent		USB-C Device Port(s)	No
Ports7InterfaceUSB 3.0Bus TypeUSB 3.0USB 3.0USB 3.0Chipset IDVIA/VLI - VL813PerformanceType and RateType and RateUSB 3.0 - 4.8 Gbit/s USB 2.0 - 480 Mbit/sConnector(s)External PortsExternal PortsUSB Type-A (9 pin) USB 3.0 (5 Gbps) USB Type-A (4 pin) USB 3.0SoftwareOS CompatibilityOS CompatibilityOS Independent		USB-C Host Connection	No
Interface USB 3.0 Bus Type USB 3.0 USB 3.0 Chipset ID VIAVLI - VL813 Performance Type and Rate USB 3.0 - 4.8 Gbit/s USB 2.0 - 480 Mbit/s Connector(s) External Ports USB Type-A (9 pin) USB 3.0 (5 Gbps) USB Type-B (9 pin) USB 3.0 USB Type-A (4 pin) USB 3.0 USB Type-A (4 pin) USB 2.0		Fast-Charge Port(s)	Yes
Bus Type USB 3.0 USB 3.0 Chipset ID YIA/VLI - VL813 Performance Type and Rate USB 3.0 - 4.8 Gbit/s USB 2.0 - 480 Mbit/s Connector(s) External Ports External Ports USB Type-A (9 pin) USB 3.0 (5 Gbps) USB Type-A (4 pin) USB 3.0 Software OS Compatibility		Ports	7
USB 3.0 Chipset ID VIA/VLI - VL813 Performance Type and Rate USB 3.0 - 4.8 Gbit/s USB 2.0 - 480 Mbit/s Connector(s) External Ports USB Type-A (9 pin) USB 3.0 (5 Gbps) USB Type-B (9 pin) USB 3.0 USB Type-A (4 pin) USB 2.0 Software OS Compatibility OS Independent		Interface	USB 3.0
Chipset ID VIA/VLI - VL813 Performance Type and Rate USB 3.0 - 4.8 Gbit/s USB 2.0 - 480 Mbit/s Connector(s) External Ports USB Type-A (9 pin) USB 3.0 (5 Gbps) USB Type-B (9 pin) USB 3.0 USB Type-A (4 pin) USB 2.0 Software OS Compatibility OS Independent		Bus Type	USB 3.0
Performance Type and Rate USB 3.0 - 4.8 Gbit/s USB 2.0 - 480 Mbit/s Connector(s) External Ports USB Type-A (9 pin) USB 3.0 (5 Gbps) USB Type-B (9 pin) USB 3.0 USB Type-A (4 pin) USB 2.0 Software OS Compatibility OS Independent			USB 3.0
Type and Rate USB 3.0 - 4.8 Gbit/s USB 2.0 - 480 Mbit/s Connector(s) External Ports USB Type-A (9 pin) USB 3.0 (5 Gbps) USB Type-B (9 pin) USB 3.0 USB Type-A (4 pin) USB 2.0		Chipset ID	VIA/VLI - VL813
Connector(s) External Ports USB Type-A (9 pin) USB 3.0 (5 Gbps) USB Type-B (9 pin) USB 3.0 USB Type-A (4 pin) USB 2.0 Software OS Compatibility OS Independent	Performance		
Connector(s) External Ports USB Type-A (9 pin) USB 3.0 (5 Gbps) USB Type-B (9 pin) USB 3.0 USB Type-A (4 pin) USB 2.0 Software OS Compatibility OS Independent		Type and Rate	USB 3.0 - 4.8 Gbit/s
External Ports USB Type-A (9 pin) USB 3.0 (5 Gbps) USB Type-B (9 pin) USB 3.0 USB Type-A (4 pin) USB 2.0 Software OS Compatibility OS Independent OS Independent			USB 2.0 - 480 Mbit/s
USB Type-B (9 pin) USB 3.0 USB Type-A (4 pin) USB 2.0 Software OS Compatibility OS Independent	Connector(s)		
USB Type-A (4 pin) USB 2.0 Software OS Compatibility OS Independent		External Ports	USB Type-A (9 pin) USB 3.0 (5 Gbps)
Software OS Compatibility OS Independent			USB Type-B (9 pin) USB 3.0
OS Compatibility OS Independent			USB Type-A (4 pin) USB 2.0
	Software		
		US Compatibility	OS independent

Special Notes / Requirements



	System and Cable Requirements	Available USB 3.0 or 2.0 port
Indicators	LED Indicators	Power
Power	Power Source	AC Adapter Included
	Input Voltage	100 - 240 AC
	Input Current	1.5 A
	Output Voltage	5 DC
	Output Current	4 A
	Plug Type	н
	Power Consumption (In Watts)	20
Environmental	Operating Temperature	0C to 85C (32F to 185F)
	Storage Temperature	-10C to 95C (14F to 203F)
	Humidity	5~90% RH
Physical Characteristics		
	Color	Black
	Form Factor	Desktop
	Material	Plastic
	Product Length	3.9 in [99.0 mm]
	Product Width	2.4 in [60.0 mm]
	Product Height	0.8 in [20.0 mm]
	Weight of Product	2.6 oz [74.0 g]
Packaging Information		

Information

Package Quantity

1



	Package Length	5.5 in [14.0 cm]
	Package Width	4.7 in [12.0 cm]
	Package Height	3.2 in [82.0 mm]
	Shipping (Package) Weight	14.5 oz [412.0 g]
What's in the Box		
	Included in Package	6 Port USB Hub
		USB 3.0 Cable
		Universal Power Adapter (NA/JP, EU, UK, ANZ)
		Instruction Manual

*Product appearance and specifications are subject to change without notice.

