

8 Port 1U Rackmount USB KVM Switch Kit with OSD and Cables

Product ID: SV831DUSBUK



The SV831DUSBUK 8-Port Rack Mount USB KVM Switch Kit offers a well-appointed KVM switch that includes all of the cables and accessories required to connect to 8 servers or PCs right out of the box, making setup convenient and simple.

The USB KVM delivers a dependable computer management tool that allows you to control up to 8 USB-connected computers from a single keyboard, mouse and display, providing maximum control through hotkey command-based switching or front panel push-buttons, with the added configurability and convenience of an On-Screen Display.

A suitable addition to server room operations, the 8-port switch can be rackmounted into 1U of cabinet space and can be cascaded with multiple KVM switches to enable control of up to 64 computers from this single switch.

This product is TAA compliant and backed by a Startech.com 3-year warranty with free lifetime technical support.

Certifications, Reports and Compatibility

Applications

- Useful in Software QA labs where testing is being done across multiple platforms
- Great for PC test/burn-in computer control, avoiding the cost of buying additional peripherals
- Central control for multiple systems in a Datacenter
- Effectively manage your server farm from a single console with cascaded units
- Manufacturing line computer control and management



Features

- Package includes 8x 6ft USB VGA KVM cables
- USB Keyboard and Mouse combo/wireless setups supported on 1 USB connection
- OSD security option allows selected KVM ports to be password-protected from unauthorized use
- Auto-scan function automatically switches between connected PCs sequentially
- Cascade configuration expands system capability
- Hotkey functions allow easy computer access
- Identifies and selects computers by the names assigned

Resolutions

• Plug-and-play system configuration

Hardware		
	Warranty	3 Years
	U Height	1U
	Audio	No
	KVM Ports	8
	PC Interface	USB
	PC Video Type	VGA
	Number of Monitors Supported	1
	Rack-Mountable	Yes
	Cables Included	Yes
	Daisy-Chain	Yes
Performance		
	On-Screen Display	Yes
	IP Control	No
	Hot-Key Selection	Yes
	Maximum Analog	1920 x 1440@60Hz (1920 x 1200@60Hz - Wide Screen)



Wide Screen Supported Yes

Maximum Number of

Users

1

Maximum Cascaded

Computers

64

Port Selection Support

Push Button, Hotkeys, and OSD (On Screen Display)

MTBF

150000 hours

Connector(s)

Console Interface(s) USB Type-A (4 pin) USB 2.0

VGA (15 pin, High Density D-Sub)

Host Connectors VGA (15 pin, High Density D-Sub)

Software

OS Compatibility OS independent; No software or drivers required

Indicators

LED Indicators Green - Power

Green - PC Online

Red - PC Selected

Power

Power Source AC Adapter Included

Input Voltage 100 - 240 AC

Output Voltage 12V DC

Output Current 1A

Center Tip Polarity Positive

Power Consumption (In

Watts)

12

Environmental

Operating Temperature 5°C to 40C (41F to 104F)

Storage Temperature -20°C to 60C (-4F to 140F)



	Humidity	0~80% RH
Physical Characteristics		
	Color	Black
	Material	Steel
	Product Length	17.2 in [43.8 cm]
	Product Width	7.1 in [18.0 cm]
	Product Height	1.8 in [45.0 mm]
	Product Depth	7.1 in [18 cm]
	Weight of Product	4.9 lb [2.2 kg]
Packaging Information		
	Package Length	23.9 in [60.6 cm]
	Package Width	10.3 in [26.2 cm]
	Package Height	4.8 in [12.1 cm]
	Shipping (Package) Weight	10.3 lb [4.6 kg]
What's in the Box	Included in Dealers	O Down LICD KV/M Constant
	Included in Package	8 Port USB KVM Switch
		Mounting Brackets
		6ft 2-in-1 USB VGA KVM cables
		Universal Power Adapter (NA/EU/UK/AU)
		User Manual

^{*}Product appearance and specifications are subject to change without notice.