

Thunderbolt 3 to 10GBase-T Ethernet Adapter

Product ID: TB310G



This Thunderbolt 3 to 10Gb Ethernet adapter connects Thunderbolt 3 enabled devices to a wired Ethernet network, with support for 10Gb/s, 5Gb/s, 2.5Gb/s, 1Gb/s and 100Mb/s Base-T speeds.

Increase your data transfer speeds by harnessing the performance of Thunderbolt 3. This Ethernet adapter adds a single RJ45 Ethernet port with 10 Gigabit support to help easily access very large files over the network at increased 10Gbps speeds.

The 5-speed Thunderbolt 3 to 10GbE adapter uses premium chipsets, providing a low-power, high-performance NBASE-T solution. The 10GBASE-T standard supports 10Gbps speeds over existing CAT6a or better cabling at distances of up to 100 m. The Tehuti TN4010 controller chipset is compliant with 802.3az Energy Efficient Ethernet and ensures peak operating efficiency with reduced power consumption in bandwidth-intensive workstation applications.

This Thunderbolt 3 NIC is an easy addition to any modern workstation. Taking up only 12 square inches of desk space and fully bus-powered, it's extremely portable with a small footprint. The fanless design means the adapter is noiseless (0dB), so you can set up in an open office space without being disruptive. It's ideal for virtually any type of workspace or environment, including remote desks and modern open-concept offices.

Developed to improve performance and security, StarTech.com Connectivity Tools is the only software suite on the market that works with a wide range of IT connectivity accessories. The software suite includes:

Mac Address Pass-Through Utility: To improve network security.

Wi-Fi Auto Switch Utility: Enabling users to quickly access faster network speeds via wired LAN.

For more information and to download the StarTech.com Connectivity Tools application, please visit: www.StarTech.com/Connectivity-Tools

This Thunderbolt 3 to 10GbE adapter is backed by a 2-year warranty and free lifetime multilingual technical support.



Certifications, Reports and Compatibility

Applications

- Home offices or remote work stations
- Modern open office setups
- For Thunderbolt 3 enabled computers

Features

- Supports auto-negotiation for 10Gb/s, 5Gb/s, 2.5Gb/s, 1Gb/s and 100Mb/s Base-T speeds
- Provides an RJ45 10Gbps Ethernet connection
- Reversible USB Type C connector with a Thunderbolt 3 interface
- Achieves 10Gbps connection over 100m with CAT6a cable
- Fanless design with aluminum chassis
- CONNECTIVITY TOOLS: Provided with this device, the application improves performance and security, featuring MAC Address Changer & Wi-Fi Auto Switch utilities

Hardware		
	Warranty	2 Years
	Bus Type	Thunderbolt 3
	Industry Standards	IEEE 802.3an (10GBASE-T) \text{br/>IEEE 802.3ab} (1000BASE-T) \text{br/>IEEE 802.3u} (100BASE-TX) \text{\text{br/>NBase-T} (5GBASE-T) \text{\text{br/>NBase-T} (2.5GBASE-T) \text{\text{\text{cpt/>IEEE 802.1q} (VLAN Tagging) \text{\text{\text{Tagging}} \text{\text{\text{cpt/>IEEE 802.3ad} (Link Aggregation)}}
	Chipset ID	Intel - Alpine Ridge DSL6340 br/>Tehuti TN4010 br/>Marvell 88X3310PA1
Performance		
	Compatible Networks	10 Gbps/5G/2.5G/1G/100 Mbps
	Auto MDIX	Yes
	PXE	No
	Full Duplex Support	Yes



Jumbo Frame Support 9K max.

Promiscuous Mode Yes

Connector(s)

Connector Type(s) Thunderbolt 3 USB-C (24-pin) (40Gbps)

External Ports RJ-45

Software

OS Compatibility Windows 7
br/>Windows 8/8.1
br/>Windows 10
Windows

11
br/>Windows Server 2008 R2
br/>Windows Server 2012 R2

Windows Server 2016

Mac OS 10.11 - 10.14

Special Notes / Requirements

System and Cable Requirements

Requires a Thunderbolt 3 port with 15W of power

Note Due to technical limitations of the IC solution, max bandwidth is

limited to about 7.5 Gbps

Indicators

LED Indicators Solid White - Thunderbolt 3 is connected to host laptop

Solid Green - RJ45 link speed of 1G, 2.5G, or 5G

Solid Orange - RJ45 link speed of 10G

Environmental

Operating Temperature 5C ~ 35C

Storage Temperature -20C ~ 50C

Humidity 20%RH ~ 80%RH

Physical Characteristics

Color Black

Form Factor Separate Cable

Material Aluminum

Cable Length 11.8 in [30 cm]

Product Length 4.0 in [10.2 cm]



	Product Width	3.0 in [75.0 mm]
	Product Height	1.1 in [29.0 mm]
	Weight of Product	11.4 oz [322.0 g]
Packaging Information		
	Package Length	6.7 in [17.0 cm]
	Package Width	5.4 in [13.6 cm]
	Package Height	3.0 in [75.0 mm]
	Shipping (Package) Weight	17.0 oz [482.0 g]
What's in the Box		
	Included in Package	Network Adapter
		Thunderbolt 3 Cable
		Travel Pouch
		Quick-Start Guide

^{*}Product appearance and specifications are subject to change without notice.