

Datasheet U6-Pro

# **UniFi6 Pro**





# Mechanical

Dimensions	Ø197 x 35 mm (Ø7.76 x 1.38")
Weight	Without mount: 460 g (1.01 lb) With mount: 600 g (1.32 lb)
Enclosure material	Plastic
Mount material	SGCC steel
Weatherproofing	IP54

### Hardware

Management interfaces	Ethernet Bluetooth		
Networking interface	(1) GbE RJ45 port	(1) GbE RJ45 port	
Button	Factory reset		
LED	White/blue		
Power method	PoE+		
Power supply	UniFi PoE switch 48V, 0.5A PoE adapter (optiona	)	
Supported voltage range	44 to 57VDC	44 to 57VDC	
Max. power consumption	13W	13W	
Max. TX power	2.4 GHz	22 dBm	
	5 GHz	26 dBm	
МІМО	2.4 GHz	2 x 2 (UL MU-MIMO)	
	5 GHz	4 x 4 (DL/UL MU-MIMO)	
Throughput rate	2.4 GHz	573.5 Mbps	
	5 GHz	4.8 Gbps	
Antenna gain	2.4 GHz	4 dBi	
	5 GHz	6 dBi	
Mounting	Wall/ceiling (included)	Wall/ceiling (included)	
Operating temperature	-30 to 60° C (-22 to 140° F)	-30 to 60° C (-22 to 140° F)	
Operating humidity	5 - 95% noncondensing	5 - 95% noncondensing	
Certifications	CE, FCC, IC, MIC		

# Software

WiFi standards	802.11a/b/g WiFi 4/WiFi 5/WiFi 6
Wireless security	WPA-PSK, WPA-Enterprise (WPA/WPA2/WPA3)
BSSID	8 per radio
VLAN	802.1Q
Advanced QoS	Per-user rate limiting
Guest traffic isolation	Supported

Zero wait DFS

#### 300+

Yes\*

\*Supported with upcoming firmware versions

802.11a	6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11b	1, 2, 5.5, 11 Mbps
802.11g	6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11n (WiFi 4)	6.5 Mbps to 600 Mbps (MCS0 - MCS31, HT 20/40)
802.11ac (WiFi 5)	6.5 Mbps to 3.4 Gbps (MCS0 - MCS9 NSS1/2/3/4, VHT 20/40/80/160)
802.11ax (WiFi 6)	7.3 Mbps to 4.8 Gbps (MCS0 - MCS11 NSS1/2/3/4, HE 20/40/80/160)

