


## MT32 Pre-Wired Floor Boxes with RCD Product Data Sheet

Product Range	UM1610 1x2 Gang RCD (Clean Earth) UM1410 1x2 Gang RCD (Std) UM1620 2x2 Gang RCD (Clean Earth) UM1420 2x2 Gang RCD (Std)	Image for reference only  
Description	MT32 Pre-Wired Floor Boxes with RCD	
Key Features	Feed: MT32 Connector 4-Pole Grey Trim and Lid Pre-wired with 13A 30mA RCD Twin Socket Reversible Lid Accepts carpets or tiles up to 6mm	
Dimensions	Floor Aperture 322mm x 222mm Carpet tile 305mm x 170mm Trim 358mm x 258mm	
Material(s)	Galvanised steel base, Polypropylene lid & trim, Zinc plated steel load plate.	
Compliance / Standards(s)	CE & UKCA Marked Low Voltage Directive 2014/35/EU The Electrical Equipment (Safety) Regulations 2016 BS 7671:2018 BS EN 61534-22:2014 BS 7288:2016	
Packaging	Recyclable	
Specification	Rated voltage (Un)	230 volts
	Operating voltage range	50 – 253V
	Rated load current	13 Amps
	Rated operating residual current (I <sub>dn</sub> )	30mA
	Rated non-operating residual current	0.5I <sub>dn</sub>
	Rated response time	<100mS for I <sub>dn</sub> <40mS for 5I <sub>dn</sub>

### Sustainability

RoHS Compliant

WEEE Compliant

